

EPICa

EN-3160 6G SATA NAS EN-3160A6T-PDC



As the number of users and the amount of data grows, how to find a storage which can offer complete data protection, good performance, with reliability and high scalability is the key for all enterprises and companies. The EN-3160 6G SATA NAS based on latest proNAS 3.0 operating system. Except for basic NAS functions, it supports a variety of advanced storage management and application features such as VAAI, HA, Thin-Provisioning, etc, and it can be deployed easily in any IT environment since it supports multiple interfaces for different host server and clients.

For data protection, EN-3160 supports RAID level 0, 1, 5, 6, 10 and 50 mode, and drives can be set hot spares, have automatically hot rebuilding and online capacity expansion within the enclosure. EN-3160 has a fully-featured backup solution including manual or scheduled backup for file, folder, and shares, and it can be backup and restore from multiple local or remote devices. And there are volume clone, snapshot, remote replication, and data copy for options, which are all designed to ensure and enhance your precious data.

Features

- Account Manager support NIS
- Allows online capacity expansion within the enclosure
- Android/iOS mobile APP for monitoring
- Backup to Cloud (Amazon S3)
- Backup/Restore from attached storage (USB/eSATA/iSCSI/RDX)
- Backup/Restore from remote share (CIFS/NFS)
- Bonjour Protocol, easily connect to NAS
- Central data and storage management
- Data backup via backup plan/schedule
- Data copy (1:1)
- EXT4 support extend over 16TB
- HA support Active-Active mode
- HA support iSCSI volume
- HA support Three nodes
- iSCSI/share volume replication
- ISO mount
- Latest volume snapshot technology
- Local and external account management, support large account import
- Online expansion file system
- Plug-in management
- Select share or file for backup/restore
- Share management and permission (support ACL setting)
- Support Internet Gateway
- Support iSCSI target for IP SAN
- Support iSCSI initiator
- Support iSCSI multi host
- Support e-mail notification, SNMP Trap/MIB and system log
- System configuration backup/restore
- Thin Provisioning
- Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS)
- Volume replication to enhance data protection
- VMware ESXi 5 iSCSI /NFS VAAI support
- Wizard-oriented GUI design
- WORM (Write Once Read Many) support CIFS/NFS



Series Technical Specifications

EN-3160A6T-PDC

NAS Hardware Specification

Intel Pentium 3.1GHz CPU or above
Cache memory : 4GB DDR3 up to 16GB
Two USB3.0 and Four USB2.0 ports
Two Gigabit Ethernet ports
Up to Sixteen 2.5"/3.5" hot-swappable 6Gb/s SATA hard drives
Real-time drive activity and status indicators
Environmental monitoring unit
Two(2) 460W 80plus hot-swappable power supplies with PFC

Environmental

Operating temp : 10°C~40°C(50°F~104°F)
Relative humidity : 10%~85% Non-condensing

RAID Controller

Highpoint RocketRAID 2720
Support RAID level: RAID 0, 1, 5, 6, 10, 50
Support drive hot spare and automatic hot rebuild
Allow online capacity expansion within the enclosure
Locally audible event notification alarm

Physical Dimension

133(H) x 482(W) x 730(D) mm

Power requirements

AC 100V ~ 240V Full range
10A ~ 5A, 47~63Hz

NAS Functionality

Storage Management

Volume management (Support XFS, EXT3 and EXT4 file system)
Disk usage statistics
Hot spare drives
iSCSI Target manager: Support LUN Mapping/Initiator Filter/Thin Provisioning
VAAI support for iSCSI/NFS

General

File Server Independent
Multiple language support
Support UPS management
Support LV encryption

System Management

Automatic IP address configuration
Web browser-based management
SNMP management and notification
Fail-free online firmware upgrade
Unicode support
Multi-node management GUI
System configuration backup/restore
Central management
Quick wizard
APP for Android/iOS monitoring

Networking

Support NIC/Trunking/Load Balance/Fail Over/802.3ad
DHCP Server/DHCP Client
WINS Server
Internet gateway

Protocols

TCP/IP, SMB/CIFS, NFS, SNMP, FTP/SFTP/FTP, HTTP, HTTPS, Telnet, SSH, AFP, WebDAV, Bonjour, TFTP

Client Operating Systems Support

Microsoft® Windows® 98/ME/NT/2000/XP/2003/Vista/2008 /Win7/Windows 2012/Win 8
Unix/Linux
Mac OS

Authentication

Local user account/group
Microsoft NT Domain Controller (PDC)

Microsoft Active Directory Authentication (ADS)

Network Information Service (NIS)

Support OpenLDAP service

Support creating users by batch

User quota management

Share level security

File level security

User ID security for NFS

Recycle bin (Samba)

File access log, audit (Samba)

Write Once Read Many (WORM)

Block Storage

iSCSI Target Support

Thin Provisioning support

VMware VAAI support

Virtualization

VMware/Citrix/Hyper-V

VMware VAAI for NFS support

Attached Storage

ISO Mount

USB/eSATA/iSCSI initiator

Data Backup / Restore

Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS)
--

Symantec BackupExec Agent (by additional installation)
--

Scheduling multi-snapshot (Support iSCSI snapshot)
--

Replication (Remote realtime data mirroring)
--

proNAS High-Availability (Three(3) nodes HA Cluster)(optional)
--

Scheduling Rsync Replication

Support NetVault backup client (by additional installation)

Support CA ARCserve (by additional installation)
--

Data copy (copy files to other share/attached storage)
--

Scheduling backup

Differential/incremental backup

iSCSI Replication

Amazon S3 backup

backup/restore from attached storage (USB/eSATA/iSCSI/RDX)
--

Support CDP server (by additional installation)

Support Apple Time Machine

Specification are subject to change without notice. All company and product names are trademarks of their respective owners.



UNIFOSA CORP.

Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975

<http://www.proware.com.tw> E-mail:info@proware.com.tw

Your Storage Solutions Partner