



Product NO.	HR-204A	HR-208A	HR-216A+
OS type/Video Compress algorithm	Embedded Linux / H.264		
Real Live frames	4ch 120 frames (NTSC) 100 frames (PAL)	8ch 240f rames (NTSC) 200 frames (PAL)	16ch 480 frames (NTSC) 400 frames (PAL)
Resolutions (fps) NTSC (Each ch adjustable independently)	1080p (1920x1080) @48 fps 720p (1280x720) @100 fps WD1 (960x480) @100 fps	1080p (1920x1080) @96 fps 720p (1280x720) @200 fps WD1 (960x480) @200 fps	1080p (1920x1080) @192 fps 720p (1280x720) @400 fps WD1 (960x480) @400 fps
Live Windows (includes 2x2 digital ZOOMIN)	1/4	1/4/9	1/4/8/9/13/16
REC. mode	Normal REC. /Schedule REC. /Motion & Alarm REC.		
REC. Quality	highest /higher /high/ normal/ low /lowest (6 types)		
Playback mode	Time & Event search /particular time period search		
Playback speed	foreard/backward : x1 / x2 / x4 / x8 / x16		
Playback channel	host : 4ch internet : 4ch	host : 8ch internet : 4ch	host : 16ch internet : 4ch
OSD functions	HDD info./Times/Camera Setting/REC. Setting/Function Menu		
Video Input (Hybrid)	4ch AHD or 4ch WD1	8ch AHD or 8ch WD1	16ch AHD or 16ch WD1
Video Output	BNC x1 / VGA x1 (1920x1080) / HDMI output (1920x1080)		
Audio input/output	4ch (RCA) /1ch		
Alarm input/output	4 IN/1OUT		
Remote Controller/Mouse	standard equipment		
Motion Detect	Motion Region 22x15 selections / 8 type sensitivity adjustable		
RS-485 function	PTZ control and keybord/host connection		
Backup	USB 2.0 /Network Backup		
3.5" SATA HDD	1 HDD (Each max. 4T)		2 HDD (Each max. 4T)
Internet functions	IE browser (max. 10 accounts) /100ch CMS		
Power	AC 100~240V(DC 12V); 50Hz/60Hz		
Weight	N.W/G.W 0.7kg/0.85kg (NOT include HDD)		N.W/G.W 1.2kg/1.5kg (NOT include HDD)
Size	300 × 65 × 270 mm		426 × 65 × 328.5mm



HR-204A



HR-208A



HR-216A+